



VACUUM CUPS WITH SUPPORTS

These traditional cup-shaped vacuum cups are suited for gripping and handling objects with flat, slightly concave or convex surfaces.

This range of widely used cups has diameters ranging from 25 to 35 mm and are normally available in standard compounds: natural para rubber N, oil-resistant rubber A and silicon S.

They can be cold fitted with no adhesive onto a nickel-plated brass support.

The support has been specially shaped to perfectly fit with the vacuum cup and is equipped with a male threaded pin to facilitate fastening to the automation. These cups are extremely easy to replace; simply request the cup indicated in the table in the desired compound when requesting the spare part.


Cups in special compounds, listed on pg. 31, and supports in different materials can be provided upon specific request in minimum quantities to be defined in the order.



VACUUM CUPS


Item	Force Kg	Volume cm ³	A Ø	B Ø	D Ø	E	F	H
01 25 10 *	1.23	1.4	12	6	25	2	3.5	8
01 30 10 *	1.76	1.8	12	6	30	1	3.5	8
01 35 10 *	2.40	2.4	12	6	35	1	3.5	8

* Complete the code indicating the compound: A= oil-resistant rubber; N= natural para rubber; S= silicon



SUPPORTS

Item	A Ø	E	F	H	SW	Support material	For vacuum cup item	Weight g
00 08 08	M6	3.5	10	14.5	3	brass	01 25 10	2.7
							01 30 10	
							01 35 10	
00 08 60	G1/8"	4.0	10	14.5	4	brass	01 25 10	5.6
							01 30 10	
							01 35 10	



VACUUM CUPS WITH SUPPORT

Item	Force Kg	A Ø	SW	D Ø	Vacuum cup item	Support item	Weight g
08 25 10 *	1.23	M6	3	25	01 25 10	00 08 08	3.9
08 25 11 *	1.23	G1/8"	4	25	01 25 10	00 08 60	6.8
08 30 10 *	1.76	M6	3	30	01 30 10	00 08 08	4.6
08 30 11 *	1.76	G1/8"	4	30	01 30 10	00 08 60	7.5
08 35 10 *	2.40	M6	3	35	01 35 10	00 08 08	5.1
08 35 11 *	2.40	G1/8"	4	35	01 35 10	00 08 60	8.0

* Complete the code indicating the compound: A= oil-resistant rubber; N= natural para rubber; S= silicon

Note: The force of the vacuum cups indicated in the table represents 1/3 of the value of the theoretical force calculated at a level of vacuum of -75 KPa and a factor of safety 3.

Transformation ratio: N (newton) = Kg x 9.81 (force of gravity)

inch = $\frac{\text{mm}}{25.4}$; pounds = $\frac{\text{g}}{453.6} = \frac{\text{Kg}}{0.4536}$

Adapters for GAS - NPT threading available on page 1.130

