







SPECIAL BELLOWS CUPS WITH SUPPORTS






Vacuum cup item	Force Kg	Bellows stroke mm	Volume mm ³	Support item	Support material	Weight g	Vacuum cup with support item	Weight g
01 11 16 *	0.23	6	319	00 08 06	AVP	2.6	08 11 16 *	3.3

* Complete the code indicating the compound: A= oil-resistant rubber; N= natural para rubber; S= silicon



Vacuum cup item	Force Kg	Bellows stroke mm	Volume mm ³	Support item	Support material	Weight g	Vacuum cup with support item	Weight g
01 11 16 *	0.23	6	319	00 08 03	brass	9.0	08 11 17 *	9.7

* Complete the code indicating the compound: A= oil-resistant rubber; N= natural para rubber; S= silicon



Vacuum cup item	Force Kg	Bellows stroke mm	Volume mm ³	Support item	Support material	Weight g	Vacuum cup with support item	Weight g
01 11 16 *	0.23	6	319	00 08 04	brass	8.1	08 11 17 F *	8.8

* Complete the code indicating the compound: A= oil-resistant rubber; N= natural para rubber; S= silicon

Note: The force of the vacuum cups indicated in the table represents 1/3 of the value of the theoretical force calculated at a level of vacuum of -75 KPa and a factor of safety 3.

Transformation ratio: N (newton) = Kg x 9.81 (force of gravity)

inch = $\frac{\text{mm}}{25.4}$; pounds = $\frac{\text{g}}{453.6} = \frac{\text{Kg}}{0.4536}$

Adapters for GAS - NPT threading available on page 1.130